




Keytouch Joystick

The Keytouch joystick has been developed to meet the specific needs and demands of the maritime market.

The joystick can be a stand alone unit or can be utilized with other Keytouch units.

It is a 3 axis joystick and offers functions like put-and-stay with a button on top. Other joysticks from the same series with other options can be used.

The Keytouch joystick can be adapted to meet individual OEM customer color, logo and design requirements.

Size (w*h)	124mm x 196mm Cutout: 114mmx186mm
Mounting	Drop-in module with mounting holes in frame, - optional back mounted
Protection Level	IP22
Interface	USB, Windows compatible
Backlit	No
Operation Temperature	-15°C~ 55°C
Storage Temperature	-20°C~ 60°C
Joystick	CALDARO ZC06B-9241A 3-AXIS, 1 switch
Certificate	 IEC 60945 Certificate no: A-11226
Optional (not certified)	<ul style="list-style-type: none"> - Can/Open BUS - Profi BUS - Field BUS - Device NET - LAN - Up to 5 more analog inputs - Up to 12 switches or indicators - Other type of joystick available



Keytouch AS
 Tverrmyra 7
 Box 54, N-3195
 Skoppum, Norway
 Phone: +47 33035800
 Fax: +47 33047244
www.keytouch.no
info@keytouch.no

Keytouch USA, Inc.
 920 Greentree Drive
 Winter Park, FL 32789
 USA
 Phone: +1 407 671 5500
 Fax: +1 407 671 6606
www.keytouch.no
info@keytouch.no