



Keytouch IEC 60945 approved Trackball panel



The Keytouch panel has been developed to meet the specific need and demand of the maritime market.

The panel is designed for the best tactical feeling using silicone buttons, which gives a soft and light feeling when operating.

The panel has red LED-backlight.

The panel can also be ordered with custom layouts, which gives even further flexibility with very little additional development, time and cost. The buttons can be individually labeled.

The panel can also be delivered with custom color, logo and design requirements.

Size (w*h)	119,4 x 188,0mm
Mounting	Drop-in module with mounting holes in frame. Or desktop version
Key switch Technology	3 silicone buttons.
Protection Level	IP22
Interface	USB type B 
OS supported	Win 8, Win 7, Win XP, Mac & Linux
Backlight	Yes. Red
Operation Temperature	-15°C~ 55°C
Storage Temperature	-20°C~ 60°C
Approvals	Tested and approved according to IEC60945. Complete testreport is available on request. 

Keytouch Technology AS
Trimveien 41A
N-3188
Horten, Norway
Phone: +47 33035800
www.keytouch.no





Installation

Mechanical

The panel is designed as a drop-in-panel, which requires a cutout in the console and 4x countersunk M4 screws. A desktop version is also available.

Connections

The keyboard is installed by using a standard USB cable type A-B – where the type B connector is connected to the panel and the type A connector is connected to PC/unit.

Device driver

The keyboard are USB HID interface compatible and there is no need for a special device driver.

LED and Backlight

The panel have integrated backlight that illuminates all keys.

